

ARTWORK SPECIFICATIONS

To ensure that you get the best results from your artwork please carefully follow the guidelines below.



FILE FORMAT

We accept only press ready PDF files.

In our experience, a correctly set-up PDF file gives the best print results across all the printing techniques we use.



RESOLUTION

All images must be at 300dpi.

Images must be at **300dpi when at 100% pixel size**. When starting a new artwork file make sure the resolution is set to 300dpi (dots per inch / pixels per inch). If the resolution of your file is lower than 300dpi, converting it to 300dpi will not improve its quality. In most cases you will need to start from scratch with a high res file. If you are scanning images it's a good idea to scan at a higher res and then convert it to 300dpi once the layout is finalised. **Please note:** if you are sourcing your images from the internet, web resolution is often 72dpi (standard screen resolution) which will print pixelated.




COLOUR MODE

The artwork must be CMYK, not RGB.

CMYK stands for **C**yan, **M**agenta, **Y**ellow, black (**K**), which are the primary colours for print. Printers use combinations of cyan, magenta, yellow and black inks/toners to print any colour you require. **RGB** stands for Red, Green, Blue, which are the primary colours for light. Your computer screen or television set use combinations of red, green and blue light to make up the colours that you see on your screen.

If your artwork is set up in the RGB colour mode the colours may not print as you see them on the screen as print is done in CMYK. Converting your file to the CMYK colour mode will give you a closer representation of how your artwork will look when printed.

PLEASE NOTE: Some colour variation is inevitable. Screen colour calibration, the type of light you work in, the type of printer being used, the type of media being printed on, the type of finish you have specified are all factors that cause variations in colour. If you have provided a proof we will try our best to match it as close as possible, taking into account the printing process and type of media being printed.



FONTS

All fonts must be embedded or outlined (converted into curves).

Embedding or outlining your fonts will ensure that your art looks right, regardless of whether or not we have the font on our system.



BLEED

All artwork (except for disc artwork) needs to have 3mm bleed, internal and external.

Bleed is extra print that is trimmed away when your artwork is cut to size. In the cutting process some movement of the printed sheets may occur. If you do not have any bleed, when page shift occurs you will get a white line where there is no print. This shift can happen either away from or into the artwork so it is always best to keep important info 3mm away from the trim edge.

Bleed is not required on the disc surface as there is no cutting involved.

Download templates from our website for exact measurements on all of our printed parts.